



(Model:FWK2416)

General Info

The advantages are as followings:

1. According to the characteristic of LED heat dissipation, the mechanical design and thermal principle are used to carry out to structural design of luminaire, combined with the material of high-thermal conductivity of high-purity aluminum alloy and the special processing technology, the effect of heat conduction, heat convection and heat radiation has been improved significantly, so that make "Wu Kong" Square series luminaires to achieve much more smaller, less weight, high light efficiency, energy saving, environmental protection and low carbon innovative products.

2. "Wu Kong" square series luminaire, integrated 10 ° shielding angle into the antiglare design, which is beautiful appearance, novel structure, easy for installation and adjustment.

Control: Standard DMX512 (1990) protocol compatible. **Application:** Suitable for lighting of Square, outdoor landscape, green landscape lighting etc.




Technical Parameter

Model	FWK2416
LED lifespan	50,000 hours
LED quantity	12 PCS
LED color(single color)	2700K/3000K/3500K/4000K/5000K/5700K/6500K
Beam angle(FWHM)	10° /15° /20° /25° /30° /45° /60° /3020° /6015°
Shielding angle	10°
Housing	Die-cast aluminum/aluminum alloy housing, Dark gray powder paint with high corrosion resistance
Glass material	5mm thickness toughened ultra-white glass
LED driver	1800mA constant current driver
Power input	100 \sim 240VAC \pm 10%,50/60Hz;24V DC
Power consumption	80W
Ingress protection	IP66
Power cable	3*1.0mm² rubber cable(High voltage);2*1.0mm² rubber cable(Low voltage)
Signal cable	CAT5-SFTP-4P(Controllable)
Control	DMX512(1990)
Classification	1;111
Anti-static	IEC61000-4(Level 4)
Ambient operating temperature	-20°C~+55 °C(Ta+10°C)
Power Factor(PF)	≧0.9
Inrush current(Max)	50A
Net weight	3.4KG



Dimension (mm)



Accessories Optional







Outer light shield Honeycomb anti-glare net Deep cylinder anti-glare shield